

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61J 2/06, 2 /00, A61B 17 /11		A2	(11) International Publication Number: WO 98/32412
			(43) International Publication Date: 30 July 1998 (30.07.98)
<p>(21) International Application Number: PCT/US98/01310</p> <p>(22) International Filing Date: 23 January 1998 (23.01.98)</p> <p>(30) Priority Data: 60/036,359 24 January 1997 (24.01.97) US</p> <p>(71) Applicant (for all designated States except US): SCIMED LIFE SYSTEMS, INC. [US/US]; One SciMed Place, Maple Grove, MN 55311-1566 (US).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): BESSELINK, Petrus, Antonius [NL/NL]; Gronausestraat 1220, NL-7534 AT Enschede (NL).</p> <p>(74) Agents: ARRETT, Oliver, F. et al.; Vidas, Arrett & Steinkraus, Suite 2000, 6109 Blue Circle Drive, Minnetonka, MN 55343-9131 (US).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published Without international search report and to be republished upon receipt of that report.</p>	
<p>(54) Title: BISTABLE SPRING CONSTRUCTION FOR A STENT AND OTHER MEDICAL APPARATUS</p> <p>(57) Abstract</p> <p>The present invention is directed to bistable cells and their use in devices, particularly medical devices such as stents, clamps and valves. An expandable stent formed of a plurality of bistable cells is described. The stent has two or more stable configurations, including a first stable configuration with a first diameter and a second stable configuration with a second, larger diameter. A valve comprising a bistable cell for use in eliminating incontinence is also disclosed.</p>			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LJ	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

BISTABLE SPRING CONSTRUCTION FOR A STENT AND OTHER MEDICAL APPARATUS

5 Background Of the Invention

There are several kinds of stents on the market with either balloon expandable or self expanding function. Balloon expandable stents are generally made from a material that can easily be plastically deformed into two directions. Before insertion, the stent is placed around the balloon section at the distal end of a catheter and
10 pressed together to reduce the outer dimensions.

As soon as the stent is brought into the body in the proper axial position it can be expanded and thereby plastically deformed by pumping up the balloon. In this final position, the stent is at its largest diameter and should function to support the surrounding tissue, preventing an undesired shape change into a much smaller diameter,
15 at least locally.

Therefore, the stent needs to have sufficient rigidity in the radial direction, but also some flexibility in the axial direction when it is in the final position. Further, the amount of material should be as small as possible and in the inner surface of the stent should not obstruct the flow through the channel (e.g., for blood) or cause too much
20 turbulence.

Problems that generally occur with these stents are as follows: After compressing the stent to its smallest diameter around the balloon, the stent will always have some elastic spring back to a slightly larger diameter, which can cause problems when the catheter is brought into the patient's body. In addition, the axial friction
25 between balloon and stent can become so small that the stent slips off the catheter. Further, a larger size stent is typically a disadvantage.

A further problem is the so called recoil of these stents. This means that after expansion by the balloon pressure, the outer diameter will always become slightly smaller as soon as the balloon is deflated. This degree of recoil can be as much as 10%,
30 which can cause migration of the stent.

A different type of stent is made of a more or less elastically expanding

structure, which has to be held on the catheter by some external means. An example of this type is a stent that is held in its constrained state by a delivery sheath, that is removed at the moment that the stent should deploy to its natural form.

Some of these stents are made of shape memory material with either
5 superelastic behavior or temperature sensitive triggering of the expansion function.

A disadvantage of these self-expanding stents is the need for the delivery sheath, causing a larger insertion diameter. The removal of the sheath also requires a sheath retraction mechanism, which has to be activated at the proximal end.

Most stents of both types further have the disadvantage of relatively large
10 length change during expansion and a poor hydrodynamic behavior because of the shape of the metal wires or struts.

Another disadvantage of some stents is the positive spring rate, which means that further expansion can only be achieved by higher balloon pressure.

The construction of prior stents is typically made in such a way that the
15 external forces, working on the stent in the radial direction, merely cause bending forces on the struts or wires of the structure.

For example, a unit cell of a Palmaz-Schatz stent, as produced by Johnson & Johnson Interventional Systems or the ACT One Coronary stent, produced by Progressive Angioplasty Systems, Inc. has in its collapsed condition a flat, rectangular
20 shape and in its expanded condition a more or less diamond-shaped form with almost straight struts (Palmaz-Schatz) or more curved struts (ACT-One).

The shape of the unit cell of such stents is typically symmetrical with four struts each having the same cross section. In addition, the loading of the cell in the axial direction will typically cause an elastic or plastic deformation of all of the struts,
25 resulting in an elongation of the unit cell in the axial direction. These unit cells have a positive spring rate. In stents based upon these unit cells the stability against radial pressure is merely dependent on the bending strength of the struts and their connections.

Summary Of the Invention

30 In this patent application a new type of stent is described with a unit cell, having a negative spring rate and a bistable function. Such a unit cell can also be used in

other medical applications. This means that it has two configurations in which it is stable without the need for an external force to hold it in that shape. The unit cell is formed using at least two different sections. One section is less pliable than the other one and acts a relatively rigid support that hinders the shape change of the more pliable section in one direction. In the other direction the pliable section can be deformed, but because of the opposing force from the rigid section, the stability of the pliable or flexible section is strongly increased.

External forces in a direction perpendicular to the most pliable section are distributed to the rigid section and the cross section of the pliable section is merely loaded in compression mode. This makes the construction much stronger than prior stents. In prior stents, all struts have generally the same cross section and mechanical properties and are merely used in the bending mode.

The construction of a stent, based upon this unit cell results in an apparatus, that can easily be elastically compressed around the balloon by finger pressure.

Below a certain critical diameter, the present stent snaps further to a stable, smallest diameter, thus holding the deflated balloon firmly on to the surface of the catheter, with an insertion diameter that is as small as possible. An additional sheath is not required, but may be used for extra safety.

After the stent has been brought into the patient's body at the proper axial position, the balloon can be inflated until the stent reaches its critical elastic equilibrium diameter. Slightly above this diameter the stent automatically expands further to its final largest diameter, where it reaches its maximum stability against radial pressure. The design enables a constant length large expansion ratio, a reliable expandability and/or a small surface ratio.

A further embodiment of this invention is the possibility of a kind of stepwise expanding stent with a range of stable diameters.

Another part of the invention is a stent with several external diameters along its length, to adapt as good as possible to the shape of the body cavity where it is placed.

Another part of the invention is the possibility to modify the stress and strain pattern in the unit cell by means of a heat treatment in such a way, that the force

displacement characteristic of this unit cell becomes asymmetrical or even exhibits a monostable instead of a bistable function, either with the expanded diameter or the collapsed diameter being the most stable condition.

Another embodiment of the invention is the modification of the geometry
5 of the cross section of some struts to achieve the symmetric or asymmetric bistable or monostable force against displacement characteristics of a unit cell.

Another part of the invention is the use of one or more unit cells in other medical applications such as, for example, an expander or a clip, either to spread a body cavity open or to clamp or hold a body part or some body tissue.

10 The invention is also directed to the use of the inventive stents in conjunction with inventive expander rings to join together two vessels.

The invention is also directed to a bistable valve having a snap-action bipositional unit cell and uses for the same, in particular, to prevent incontinence.

The invention is also directed to multistable cells and their use in medical
15 devices.

Description of the Construction.

The construction of the present stent includes a series of elements with an arrangement of unit cells that enable the stability in a special way. Each unit cell exists
20 out of at least two distinct, mechanically connected sections with different mechanical behaviors. One section acts as a relatively rigid support for the more flexible counteracting section. The more flexible section is responsible for most, if not all, of the expansion of the stent. There are several ways to manufacture a stent based upon this principle and it can be made from several materials, like polymers, composites,
25 conventional metals or shape memory alloys with superelastic behavior or with temperature sensitive behavior.

It can be made from an arrangement of wire or strip, welded together at specific places. Another possibility is metal deposition in the desired pattern onto a substrate or the use of sintering of prealloyed powder.

30 A further method is making the stent from a tubular shaped starting material, with a pattern of slits or slots made in the wall by means of etching, grinding,

cutting (e.g., with a laser, water, etc.), spark erosion or any other suitable method. The pattern can also be made in a flat plate and then welded, brazed or crimped to a more or less cylindrical shape or a cylindrical mid section with two conical ends with larger diameters.

5

Brief Description of the Drawings

Fig. 1 shows the principle of a bistable mechanism;

Fig. 2 shows the force-displacement characteristic of the mechanism of Fig. 1;

10 Fig. 3 shows another bistable mechanism with an asymmetric bistability;

Fig. 4 shows the force-displacement characteristic of the mechanism of Fig. 3;

Fig. 5a shows an inventive tubular stent in the stable, fully collapsed configuration;

15 Fig. 5b shows an inventive tubular stent in the stable fully expanded configuration;

Fig. 6 shows a part of a stent with one bistable unit cell, drawn in the stable expanded shape;

20 Fig. 7 shows the part of the stent of Fig. 6 near its elastic bistable equilibrium position;

Fig. 8 shows the part of the stent of Figs. 6 and 7 in its stable collapsed shape; and

Fig. 9 shows a larger section of the stent of Figs. 6 and 8, showing some unit cells in the collapsed shape and some unit cells in the expanded shape.

25 Fig. 10 shows an inventive stent formed of a plurality of smaller inventive stents joined together with flexible connectors.

Fig. 11 shows a partially expanded inventive stent having more than one type of bistable unit cell;

30 Fig. 12 shows an inventive stent having a range of diameters along its length;

Fig. 13 shows an inventive expansion ring in expanded state;

Fig. 14 shows the expansion ring of Fig. 13 in contracted state;

Fig. 15 shows an inventive stent joining two vessels together and further secured with inventive expansion rings, the stent exterior to the vessels;

Fig. 16 shows a cross-sectional view of Fig. 15 along section line 16-16;

5 Fig. 17 shows an inventive stent joining two vessels together, the stent interior to the vessels;

Fig. 18 shows two vessels joined together with an inventive expansion ring and a clamp

Fig. 19 shows a bistable valve in the closed position;

10 Fig. 20 shows the bistable valve of Fig. 19 in the open position;

Fig. 21a shows a multistable cell in the fully contracted state;

Fig. 21b shows the multistable cell of Fig. 21a in the fully expanded state;

Fig. 22a shows another multistable cell in the fully contracted state;

Fig. 22b shows the multistable cell of Fig. 22a in the fully expanded state;

15 Fig. 23 shows several unit cells as shown in Figs. 21a,b joined together and in the fully expanded state;

Fig. 24a shows several unit cells as shown in Figs. 22a,b joined together and in the contracted state;

20 Fig. 24b shows the interconnected cells of Fig. 24a in fully expanded state;

Fig. 24c shows the interconnected units cells of Fig. 24a in the process of expanding; and

Fig. 24d shows several strips of interconnected cells as in Figs. 24a,b joined together and in the process of expanding.

25

Detailed Description of the Drawings

Fig. 1 shows the principle on which the stent is based, Fig. 1a shows a rod 1 with a length L, which is compressed in its axial direction unit; it reaches its buckling stress. Then the central part of the rod will bend out in a sideways direction, either to position 2 or 3 (dashed lines in Fig. 1b). When the axial displacement L of the ends of the rod is held stable by external clamps 4, it is possible to move the central section of

30

the rod between the two stable positions 2 and 3. This movement is in a direction X, perpendicular to the original length axis A-A of the rod. All positions between the stable positions 2 and 3 are unstable. In Fig. 1b the central part of the rod has to rotate over an angle β before the rod can be moved in direction X. Fig. 1c shows a second order curvature in rod 1, which occurs when the rotation over angle β is opposed by clamping
5 the central part of rod 1 and maintaining this part parallel to the axis A-A.

Fig. 2 shows the force F as a function of displacement X, with X displayed in the horizontal direction. The rod is moved from the upper 2 to the lower 3 stable position of Fig. 1. The force increases rapidly from zero to Fmax. At that moment
10 the onset of either the first or second order curvature of Fig. 1b and 1c is reached. Further displacement in direction X costs less force, because this spring system has a negative spring rate. The force even becomes zero in the mid position and further movement occurs automatically. It can be seen in Fig. 2 that the system is completely symmetrical and the force needed to move back from the lower to the upper position has the same
15 characteristic.

Fig. 3 shows rod 5, which will have an asymmetrical force displacement characteristic, because it already has a preset curvature, even in the unloaded position, where the length is already $L - \Delta L$. This can be achieved by prior plastic deformation, heat treatment or the use of an asymmetrical geometry of the cross section of the rod (not
20 shown). The rod 5 in Fig. 3 can be mounted between two clamps on a length $L - \Delta L$, and if it is elastically deformed in the same way as the rod in Figs 1b and 1c, it will have a different stress distribution in the cross section in end position 2 and 3, compared to the rod of Fig. 1. This means that the rod has become a preferred unloaded stable position, shown in Fig. 3.

Fig. 4 shows the asymmetrical force-displacement characteristic of the precurved rod of Fig. 3. The initial displacement from the stable upper position needs a starting force F1 and if the rod is in its stable lower position the starting force in the opposite direction is only F2, being smaller than F1. Force F2 can be made as small as desired, even zero or negative, but needs to have a positive value if stability of the lower
30 position is required.

Figs. 5a and 5b show the general appearance of an inventive tubular stent

in fully contracted and fully expanded configuration respectively. The stent, in its fully contracted state shown generally at 50 and in its fully expanded state shown generally at 60, is comprised of a plurality of interconnected bistable unit cells (shown in the expanded state at 64 in Fig. 5b). The bistable unit cells are formed from a first relatively rigid segment 52 (66 in Fig. 5b) and a second relatively flexible segment 54 (68 in Fig. 5b), joined together at ends 70 and 72. Second relatively flexible segments 68 are interconnected with adjacent relatively rigid members 66. Adjacent cells in the longitudinal sense (the longitudinal axis is denoted by reference numeral 75) are joined at ends 70 and 72. By applying a uniform radially outward or inward force, the stent may be switched directly from a fully contracted to a fully expanded configuration or vice versa.

Fig. 6 (corresponding to inset 6 in Figure 5b) shows a small part of a stent such as that shown in Figs. 5 which uses the bistable function of a unit cell, according to the present invention. The drawing shows a horizontal line A-A, which is parallel to the central axis of the stent. There are two series of sinusoidal segments with distinct size (see also Fig. 9 for an overview). The segments 7 and 9 have a relatively large cross section. Only segment 9 is shown entirely. The segments 9 and 10 have a relatively smaller cross section, and here only segment 8 is entirely shown. The segments are interconnected for example welded, at joints 11 and 12.

Because of the difference between the cross section of segment 8 and 9, the deformation force of segment 8 is much lower than for segment 9. Therefore, segment 9 can be considered as a relatively rigid clamp, like the clamps 4 in Fig. 1b opposing relative displacement between the joints 12 in the axial direction, parallel to axis A-A. In contrast, segment 8 acts as a flexible rod, like rod 1, described in Fig. 1 or rod 5, described in Fig. 3. This combination of segments 7 and 8 or 9 and 10 defines a unit cell, acting as a bistable spring system with a force-displacement curve F-X like the described curves of Fig. 2 and 4, depending on the unloaded condition and geometry of the segments. Alternatively, instead of using segments or struts of different diameter, the segments can have the same diameters (i.e., cross sectional area) and exhibit different strengths or rigidity and still accomplish the same effect. One way to obtain such differences in strength or rigidity would be to use different materials for the segments.

Another way would be to use the same material, like a metal, for all the segments but selectively strengthen (e.g., by heat treating) those segments that need to be rigid. It should be noted that heat treatment will not strengthen all materials. Nitinol, for example becomes more pliable as a result of heat treatment. This property of Nitinol can be exploited, however, to render one section of Nitinol more pliable relative to a second, non-heat-treated section of Nitinol.

Fig. 7 shows the same part of the stent (as depicted in Fig. 6) near the elastic equilibrium position. Segment 8 has been deformed into the direction X, caused by force F, but segment 9 has almost its original shape, because of its larger rigidity.

Fig. 8 shows the same unit cell of the stent of Figs. 6-7 after it has been pressed through the elastic equilibrium position. It automatically snaps into its stable position of Fig. 8. This snapping force can be strong enough to hold a deflated balloon tight on the catheter shaft (not shown), depending on the mechanical characteristics (e.g., the strength) of the material(s) used to make the segments. With the geometry shown in these figures, the segments 8 and 9 fit close together, taking up a minimum amount of space when the stent is in its smallest stable diameter.

Fig. 9 shows a section of the stent of Figs. 5, flattened for illustrative purposes, showing several flexible segments in the collapsed stable shape (segments 14, 18 and 20) and one segment element 16 in the expanded stable shape. Segments 13, 15, 17, and 19 are relatively rigid segments and substantially maintain their original shape. The distance between two relatively rigid segments is shown as (h) in the collapsed stable shape and (H) in the expanded stable shape. The value of the displacement (H-h) in the direction X depends on the height of an expanded unit cell or amplitude of the segments and the size of the connecting joints. The described part of the stent is shown as a flat surface, but it may be clear that a cylindrical stent such as that shown in Figs. 5 is shaped if segments 13 and 20 are directly connected to reach other with joints 21. In other words, the stent is shown separated along the joints 21 and in a flattened condition.

The range of stable diameters of the stent changes with the value $(H-h)/\pi$, each time that a flexible segment snaps from the collapsed stable position to the expanded stable position. The result is a stent with an extremely rigid surface at all diameters being able to withstand the external forces better than with conventional stents.

In the length direction, the flexibility of the stent can be increased by disconnecting several unit cells from their neighbor unit cells, for example, by cutting the center of one or more joints while maintaining the several joint pieces as joints.

Another method to increase flexibility is to change the geometry of
5 several sections of the unit cells in the length direction from the relative flexible to the relative rigid shape several times along the total length of the stent. In other words, referring to Fig. 9 one or more or each of the segments 13 - 20 could be constructed with larger and smaller diameter (or otherwise flexible and rigid) sections which alternate after each joint 21.

10 Another possibility, as shown in Figure 10 is the use of a series of short multistable stents 100 aligned lengthwise end to end and connected with flexibility joints 104 having the same or a different geometry or configuration as the joints forming individual unit cells.

The scope of the invention should include all types of material. One of
15 the most interesting materials is superelastic Nitinol, because of its large elastic strain, well defined stress values, caused by their plateau stresses and the possibility to define the desired curvature into the metal by means of a heat treatment. A stent of Nitinol can be made by forming slits or slots in a tube, while in its collapsed or smaller stable diameter. The slotted tube is then expanded by a separate shaping tool and heat treated
20 on this tool to define the expanded stable diameter as the unstrained shape.

In a more general sense, the present invention is directed to a device having a plurality of stable configurations. The device is comprised of a plurality of interconnected multistable cells. The cells include one or more relatively rigid sections and one or more relatively flexible sections interconnected so as to define a cell structure
25 in the form of a multistable spring system having a plurality of stable configurations. In a preferred embodiment, the cells comprise a first arcuate member having first and second ends and a second arcuate member having first and second ends, the first end of the first member in communication with the first end of the second member, and the second end of the first member in communication with the second end of the second member. It should be noted, however that members need not be rigorously arcuate.
30 Other shaped members, including relatively straight members are contemplated as well.

The invention, in particular, contemplates bistable cells, that is cells having two stable configurations. In one such cell, the distance between corresponding points on the first and second sections is larger in the first stable state of the cell than in the second stable state of the cell. The cells themselves are constructed and arranged so that the device itself is at least bistable and possibly multistable. One such device, a cylindrical stent having two or more configurations with an initial diameter size and a final larger diameter size has been described above. However, multistable stents are also contemplated. Thus, for example, a stent may be constructed in which the cells are designed and arranged to provide a range of diameters in step-wise fashion. One such way this may be accomplished would be to employ several different types of cells in the stent, each type of cell having a different spring constant so that depending on the amount of force used, the stent would assume a different diameter. Such a stent in a partially expanded state is shown schematically in Fig. 11. A partially expanded stent is shown generally at 120. The stent is comprised of relatively rigid segments 123, 127, 131 and 135 which substantially maintain their original shape, and relatively flexible segments 125, 129, and 133. The segments are interconnected, with joints 122. As depicted, first flexible elements 125, and 133 are in an expanded configuration while second flexible element 129 is in a contracted configuration. By applying a radially outward or tangential force, flexible element 129 may be flipped to its fully expanded configuration resulting in a stent (not shown) with a larger diameter. As shown in Fig. 11, cells 138 are larger than cells 136 even in the contracted state. First flexible elements 125 and 133 are characterized by a different degree of flexibility than second flexible element 129.

Another form of stent, as shown generally at 150 in schematic Fig. 12, has an first diameter at a first end 152, a second diameter at a second end 154 and one (or more) intermediate diameters in a region 156 between first end 152 and second end 154, the intermediate diameter differing from the first and second diameters. The interconnected cells in such a stent, as shown generally at 150 in Fig. 12 may all have the same force constant and hence be openable all at once with the application of the necessary force or there may be several different types of cells, each with their own force constant. In order to achieve the multiplicity of diameters, cells of differing sizes may be

used. In one embodiment of this type of stent, the first and second diameters are the same while in another embodiment, the first and second diameters differ.

The present invention is also directed to a method of implanting an expandable stent having a plurality of stable configurations. The method comprises the steps of applying the stent to an expanding means on a catheter, delivering the stent to a desired bodily location, expanding the expanding means so as to expand the stent from a first stable configuration to a desired second stable configuration, the second stable configuration having a larger diameter than the first stable configuration, and deploying the expanded stent at the desired bodily location. The expanding means may be a balloon, a mechanical device on or in the catheter, a heat source where the cells can be induced to change states by heating or any other suitable expanding means. The stent may be applied to the balloon in the first stable configuration or may be applied in the second stable (expanded) configuration during the applying step. In the latter case radially inward pressure may be applied to the stent so as to urge the stent into the first stable configuration to snap it onto the catheter. Where the stent has additional stable states, the stent may be applied to the balloon in an intermediate stable state in which the diameter of the stent is intermediate between the diameter in the first state and the diameter in the second state. Again, the stent may be locked on the expanding means by further applying a radially inward pressure.

A further object of the invention is the use of a single bistable unit cell as an expander (expansion ring), that can be brought into a narrow place and then triggered to snap back into its expanded stable shape. As shown in Fig. 13 an expansion ring shown generally in its expanded state at 250 consists of a first rigid member 254 having first 258 and second 262 ends and a second more flexible member 266 having first 270 and second 274 ends. First end 258 of first member 254 is connected to first end 270 of second member 266 and second end 262 of first member 254 is connected to second end 274 of second member 266. Fig. 14 depicts the expansion ring of Fig. 13 in its contracted state. Second member 266 is seen to be in a second stable position.

Another object of the invention is the use of a single bistable loop (unit cell) as a clip, that can be used to clamp on an artery, fallopian tube or any other body part, to close or hold it for some time. For such a clip it may be desirable to define the

collapsed stable shape as the unstrained shape, because the collapsed stable shape has to be the most stable one. In the collapsed state, the clip would resemble the collapsed expansion ring of Fig. 14. A triggering means would be used in conjunction with the clamp to switch the bistable loop from one state to another. The triggering means may be pneumatic, hydraulic, mechanical, thermal or electromechanical means. Examples of such triggering means include a human hand applying force to the bistable loop, and the application of heat to the loop. Other triggering means include pulling on the device, pushing on the device, bending the rigid section of the device or releasing a restraint holding the flexible member in place.

Another part of the present invention involves constructions between one or more ring-shaped elements according to the present invention, combined with a tubular sleeve that is reinforced or held open with such elements. An example is a so-called graft stent made of a polymer with one or more expansion rings. The expansion rings may consist of the above-described bi-stable cells. The surface of the stent comprises a skin mounted on the expansion rings. In mounting the skin, the skin may surround, be in or between the expansion rings. The skin may be human or animal skin, a polymeric material or any other suitable bio-compatible material. Such a stent may comprise one or more expansion rings, such as a first expansion ring at a first end of the stent and a second expansion ring at a second end of the stent. The stent may be of constant diameter along its length or may have a first diameter at the first end and a second diameter at the second end.

The present invention is also directed to a stent having an unexpanded configuration and an expanded configuration, and comprising a plurality of generally longitudinal, wave-like first members characterized by a first wavelength, and having peaks and troughs and a plurality of generally longitudinal wave-like second members characterized by a second wavelength, and having peaks and troughs. The wavelengths of the first and second longitudinal members are substantially equal. The second members are capable of stably assuming two positions, a first position corresponding to the unexpanded configuration in which the first and second members are in phase and a second position corresponding to the expanded configuration, in which the first and second members are 180° out of phase. The first members are more rigid than the

second members. The first and second longitudinal members are disposed on the surface of the stent such that the longitudinal first and second members alternate. In the unexpanded state, each peak of each first member is connected to one adjacent peak of a second member in a region of attachment and each trough of each first member is
5 attached to one adjacent trough of a second member in a region of attachment, as can be seen from Fig. 9. The regions of attachment are separated along the longitudinal direction by one wavelength. The so described stent can be snapped from the unexpanded configuration to the expanded configuration by applying a radially outward force and similarly can be snapped from the expanded to the unexpanded configuration
10 by applying a radially inward force. While such stents may be used internal to a bodily vessel, it may also be used external to vessels to join two vessels together.

The invention also contemplates a method of joining together two vessels comprising the steps of delivering an inventive stent in an unexpanded configuration in a first stable state to a bodily site, expanding the stent to a second stable state, the diameter
15 of the stent in the second stable state exceeding that of the vessels to be joined and placing the stent over the vessels to be joined. The stent may then be contracted to a third stable state, the stent in the third stable state having a diameter intermediate between the diameters of the stent in the unexpanded state and in the second stable state. The stent may further be secured to the vessel with the aid of one or more of the above-
20 described expansion rings (a bistable loop). One or more expansion rings, such as that depicted in Figs. 13 and 14 or small clamping stents (such as that formed from the strip shown in Fig. 23) may be delivered to each side of the stent in a contracted state and deployed so as to clamp the vessels between the ring(s). Multiple rings may be used for additional clamping. As shown generally at 300 in Fig. 15, a first vessel 304 and a
25 second vessel 308 are joined together with inventive stent 312. Vessel 304 overlaps stent 312 in a first overlap region 316 while vessel 308 overlaps stent 312 in a second overlap region 320. Vessel 304 is clamped between expansion ring 324 (shown in the expanded state) and stent 312 while vessel 308 is clamped between expansion ring 328 (shown in the unexpanded state for illustrative purposes only) and stent 312. the dotted lines
30 associated with expansion ring 328 illustrate expansion ring 328 in its expanded state. It should be additionally noted that Fig. 15 provides a cut-away view of vessels showing

the rings contained therein. Fig. 16 shows a cross-sectional view of Fig. 15 along section line 16-16. Vessel 304 is shown sandwiched between stent 312 and expansion ring 324.

In another embodiment, as shown in Fig. 17, a first vessel 404 and a second vessel 408 are joined together by a stent 412. First end 416 of stent 412 rests in vessel 404 while second end 420 of stent 412 rests within vessel 408. Optional clamps (such as a small portion of a collapsible inventive stent shown later in strip form in Fig. 23) 424 and 428 residing on the outside of vessels 404 and 408 clamp the stent to the vessel. Additional clamps may be used as needed.

In another embodiment, a combination of the embodiments of Figs 15 and 17, the first end of the stent may protrude from one of the vessels and the second end of the stent may extend over the second vessel. Again, clamps and expansion rings may be used to further secure the stent to the vessels.

In another embodiment, as shown in Fig. 18, vessel 454 and vessel 458 are held together by an expansion ring 462 internal to the vessel and a clamp 466, consisting of, for example, a small section of collapsible stent, the stent chosen so that the diameter of the stent in a collapsed state affords a snug fit with vessels 454 and 458 and expansion ring 462. Either the expansion ring or the clamp, but not both, may be replaced by a suitable support such as a rigid collar.

The invention also contemplates a method of joining together two vessels comprising the steps of delivering an inventive stent in an unexpanded configuration in a first stable state to a bodily site, placing two bodily vessels over the stent and expanding the stent to a second stable state, the diameter of the stent in the second stable state exceeding that of the vessels to be joined. The diameter of the stent in the second stable state is preferably chosen so that the vessels fit snugly over the stent. The delivery of the stent may be accomplished by delivering the stent in an unexpanded configuration through a bodily vessel and subsequently expanding the stent to rest snugly in the vessels to be joined (where a portion of the stent resides in a vessel), or by expanding the stent to its most expanded state, placing the stent over the vessel and then contracting the stent to an intermediate state over the vessel. The collars and expansion rings mentioned above may similarly be delivered. Alternatively, the stent, collars and expansion rings may be delivered by surgically exposing the vessel in question.

The present invention is also directed to a bistable valve. The valve, as shown generally at 600 in Fig. 19 includes a snap-action bipositional unit cell shown generally at 604 located within a conduit 606. Snap-action bipositional unit cell 604 consists of a (substantially arcuate) flexible member 608 having a first end 612 and a second end 616. First end 612 is in communication with a triggering means 620 which is supported, in turn by a support means 624 emerging from the inner surface of conduit 606. Second end 616 of flexible member 608 is anchored to stop surface 628 which extends across conduit 606. Support means 624 and stop surface 628 must be sufficiently rigid to hold flexible member 608 in place and must be more rigid than flexible member 608. Stop surface 628 extends substantially obliquely across conduit 606 in oblique regions 630 and has a opening 632 within in longitudinal region 634 to allow the flow therethrough of a fluid. Although opening 632 is oriented along the longitudinal axis 636 of conduit 606, those of ordinary skill in the art will recognize other possible orientations of the opening and stop surface. Valve closure member 640, actuated between open and closed positions by flexible member 608, is constructed and arranged so as to block the flow of fluid through opening 632 when flexible member 608 is in the closed position. When flexible member 608 is in the open position, as depicted in Fig. 20 valve closure member 640 no longer obstructs opening 632, thereby allowing the flow of fluid therethrough.

While triggering means 620 may be any suitable mechanical, hydraulic, pneumatic, or thermal based trigger known in the art at present or in the future, in a preferred embodiment, triggering means 620 is a piezoelectric element. In operation, if the piezoelement shown in Fig. 19 at 620 is not activated, valve closure member 640 is closed. Activation of piezoelement 620, as shown in Fig. 20 causes a small shortening in the longitudinal length (denoted by Y in Fig. 15) of piezoelement 620 which in turn releases flexible member 608 from its first position. With member 608 released, valve closure member 640 is free to open under the pressure transmitted from the fluid. Member 608 assumes a second, inverted, position, as depicted in Fig. 20. While the fluid pressure maintains member 608 in its second position, even in the absence of any fluid, member 608 remains in its second position, as depicted in Fig. 20 if the triggering is turned off and piezoelement 620 assumes its original length. Valve closure member 640

may be closed again, in the absence of fluid, by a subsequent triggering of piezoelement 620 allowing member 608 to transition to its second (closed) position which is the preferred position of member 608. Member 608 has been treated to receive a preferred position as shown in Fig. 3.

5 The valve depicted in Figs. 19 and 20 may be applied to medical and non-medical devices. It is, in particular, an aim of the present invention to apply the inventive bistable valve to the control of urinary incontinence. In a patient with incontinence, the above described valve may be implanted in the urethra using any suitable means including the use of the above-described expansion rings to clamp the valve to the
10 urethra. Although the valve in the default state is closed, the valve may be triggered when the bladder is full, to void the bladder. Upon voiding the bladder, the valve may be triggered again to close it. Another such application is to employ the inventive valve in conjunction with a shunt. The shunt may be activated by triggering the device and similarly may be closed by triggering the device.

15 Of course the valve may be used in other medical and non-medical applications as well.

 In addition to the bistable unit cells disclosed above, bistable unit cells and more generally, multistable unit cells of other shapes are also contemplated by the present invention. Figs. 21a and 21b are schematic representations of another
20 embodiment of an inventive hinged multistable cell in its contracted and expanded states, respectively. The contracted cell, shown generally at 700, and the expanded cell, shown generally at 705, consist of four interconnected relatively rigid members. Two side members 709 are connected to opposite ends of top member 713 via hinges 715. Side members 709 are connected at their opposite ends to opposite ends of bottom member
25 717 via hinges 719. Preferably, the hinges are elastic or plastically deformable. The hinges may be fixedly attached to the side, top and bottom members or may be integral with these members. In the latter case, the hinges may be formed by removing material from the cell in the region of the hinges so that the hinges are thinner or have a different geometry from the side, top and bottom members. In the process of transitioning from
30 the expanded to the collapsed state, bottom member 717 opens slightly. The cell of Figs. 21a,b also has two additional intermediate states in which one or the other (but not both)

of side members 709 and top member 713 are collapsed downward.

A hexagonal hinged multistable unit cell is shown schematically in Fig. 22a in the collapsed state and in Fig. 22b in the expanded state. The cell, shown generally at 750, consists of top member 754 and bottom member 758, and upper side members 762. Two upper side members 762 are connected to opposite ends of top member 754 via hinges 756. Upper side members 762 are connected to bottom member 758 via hinges 768. Bottom member 758 is shaped like a 'U' with the two uprights of the 'U' modified to lie at oblique angles with respect to the bottom part of the 'U'. As with the previously discussed inventive cells, hinges 756 and 768 may be elastic or plastically deformable and may be fixedly attached to the members or integral with the members. The hexagonal unit cell exhibits multiple stable states. In addition to the fully expanded and fully contracted states shown in Figs. 22a and 22b, the hexagonal cell can also achieve two intermediate stable configurations in which only one of the two upper side members 762 is collapsed inward along with top member 754.

The above described hinged multistable cells may be used in any of the above discussed applications e.g. to form stents, clamps, clips, expander rings, bistable valves.

In one such application a ring or stent is formed of the hinged cells of Figs. 21a and 21b. As shown in Fig. 23, a series of unit cells of the type depicted in Figs. 21 are joined together so that the top member of a cell forms a portion of the bottom member of an adjoining cell. As depicted, top member 814 of cell 810 forms a portion of bottom element 818 of cell 820. Similarly, top member 824 of cell 828 forms a portion of bottom element 832 of cell 836. Although the ring or stent in Fig. 23 has been cut for illustrative purposes, the two ends 840 and 844 are normally joined together with a portion of lower member 848 of cell 852 serving as an upper member for cell 856. The ring so formed has a range of stable states including a fully expanded state and a fully contracted state. Where the individual cells are made identically, only the fully expanded states may be accessed by the application of a uniform radially outward force to the stent in the fully contracted state. It may serve as a clamp or collar, an expansion ring or a stent. Larger stents may be formed by interconnecting a plurality of such rings.

Similar products may also be formed from other multistable units cells.

Figs. 24a and 24b illustrate one such possibility schematically in which hexagonal unit cells such as those shown in Figs. 22a, b may be joined together to form a ring. The top member 884 of each cell 880 is joined with a the bottom portion 886 or modified 'U' shaped bottom member 890. Although shown in strip form in Figs. 24a and 24b, end 894 can be joined to end 898 to form a ring. The strip of Fig. 24a is shown in fully expanded state in Fig. 24b. Adjacent cells 880 are seen in their expanded state. For the sake of completeness, the hinges are designated 902. Fig. 24c shows one cell 920 in the process of expanding and one already expanded cell 924. The cells 920 and 924 are joined at bottom member 928 and top member 932. Hinges are shown at 936. Multiple strips may also be joined together so as to form a stent whose length is a multiple of the length of the unit cell. In such a case, upper side members of adjacent cells would be joined together. This is illustrated in Fig. 24d which, like Fig. 24c shows cells 940 in the expanded state and cells 944 in the process of expanding. Upper side members 948 are shown by dashed lines. Adjacent strips of interconnected cells 952 are joined together by upper side members 948 as well as by oblique regions 956 of bottom members 960.

It should be noted that the inventive devices of the present application may be used on a temporary basis or on a permanent basis in the body. Thus, for example, permanent stents and clamps are contemplated, as are removable stents and clamps.

It should further be noted that in expanding some of the inventive multistable cells, there may be components of expansion/contraction in a direction perpendicular to the direction of the force applied to expand the cells.

Finally, for the purposes of this application, the term 'multistable' is intended to include 'bistable'.

In the described drawings and text only some examples of different embodiments have been given. While the stents of the present invention can appear similar to prior stents, the mechanical results are completely different due to the special combination of a rigid section and a more flexible section in the same unit cell. Of course there are, beside the illustrated sinusoidal shape many other possible basic shapes for the unit cells, with similar characteristic behavior.

From the above disclosure of the general principles of the present

invention and the preceding detailed description, those skilled in this art will readily

comprehend the various modifications to which the present invention is susceptible. It is intended for the coverage of the present application to include different geometries, different constructions and different combinations of one or more materials to obtain the same basic mechanical behavior as exhibited by the above described examples.

What is claimed is:

1. A medical device containing at least one unit cell, existing from at least two different segments, one segment being relatively flexible and the other segment being relatively rigid, mechanically connected in such a way, that the more rigid segment
5 hinders the deformation of the more flexible segment in one main direction, resulting in a structure that can be deformed into the other main direction, about perpendicular to the first main direction, between a first more or less stable collapsed shape and a second more or less stable expanded shape.
2. A unit cell as claimed in claim 1, having a symmetrical load-displacement
10 characteristic around the equilibrium center position.
3. A unit cell as claimed in claim 1, having an asymmetrical load-displacement characteristic around the equilibrium position, with the expanded shape being the most stable one.
4. A unit cell as claimed in claim 1, having an asymmetrical load-displacement
15 characteristic around the equilibrium position, with the collapsed shape being the most stable one.
5. A unit cell as claimed in claims 1 to 4, where the different characteristics are mainly determined by differences in geometry of said flexible and rigid segments.
6. A unit cell as claimed in claims 3 to 5, where the different characteristics are only
20 or also determined by differences in the unstrained shape of the segments, by prior plastic deformation and/or final heat treatment and/or by the use of difference material for the distinct segments.
7. A unit cell as claimed in claims 1, 2, 4, and 6, used as a clip to clamp or hold a body part or several body parts.
- 25 8. A unit cell as claimed in claims 1, 2, 3, 5, and 6, used as an expander to spread a body cavity open or hold several body parts apart.
9. A structure made from an arrangement of unit cells as claimed in claims 1 to 6, in such a way that seen along the most deformable direction of the unit cell, each or most of the flexible segments of the unit cells are connected to the rigid segments of the adjacent
30 unit cell by means of joints, located at or near the point of maximum deflection of each flexible segment.

ISA/EP

RECTIFIED SHEET (RULE 91)

ISA/EP

10. A stent, made from a structure as claimed in claim 9, by connecting specific segments of different unit cells, thus erecting a hollow, collapsible and expandable body, with different stable diameters, depending on the amount and location of unit cells that are in their stable expanded shape.
- 5 11. Each of the products as claimed in claims 1 to 10, at least locally made from a plastic deformable material or an elastical deformable material.
12. Each of the products as claimed in claims 1 to 11, made from a polymer, a metal, a composite, a shape memory material with superelastic behavior, a shape memory material with temperature sensitive behavior or a combination of two or more of these
- 10 materials.
13. Each of the products as claimed in claims 1 to 12, where an increased flexibility within a unit cell is obtained by locally changing the geometry of the most flexible section along its length.
14. Products as claimed in claim 13, where the increased flexibility is caused by
- 15 elastic hinges.
15. Products as claimed in claim 13, where the increased flexibility is caused by plastic hinges.
16. A stent as claimed in claims 10 to 15, where the flexibility between adjacent unit cells in tangential and/or axial direction is increased by separating these unit
- 20 cells by plastic or elastic deformable hinges.
17. A stent as claimed in claims 10 to 16, where the flexibility between adjacent unit cells in tangential and/or axial direction is increased by separating these unit cells completely from each other.
18. A stent as claimed in claims 16 and 17, where a series of short stents with bistable
- 25 unit cells are connected in axial direction by flexible joints with different geometry.
19. A stent as claimed in claims 10 to 18, where a number of bistable unit cells is combined with unit cells with a different characteristic.
20. A stent as claimed in claim 19, where the cells with different characteristic are balloon expandable, self-expanding or temperature sensitive.
- 30 21. One or more stents as claimed in claims 10 to 20, used in combination with a graft stent.

22. A stent as claimed in claim 21, where the bistable stent is used to press a graft stent against a second stent that at least partly surrounds the graft stent and the bistable stent.
23. A stent as claimed in claims 10 to 22, that is made removable by collapsing it
5 back to its smallest stable diameter before removal.
24. A stent as claimed in claims 10 to 23, that contains not only unit cells that expand in tangential direction, but also in different directions.
25. A stent as claimed in claims 10 to 24, that does not only have a cylindrical section, but also tapered sections.
- 10 26. A stent as claimed in claims 10 to 25, where at least some unit cells have an asymmetrical load-displacement/characteristic with a collapsed shape that it not stable.
27. A medical device using a unit cell as claimed in claims 1 to 9, where the triggering to move from the collapsed shape to the expanded shape or vice versa is caused by pneumatic, hydraulic, mechanical or electromechanical means.
- 15 28. A stent as claimed in claims 10 to 26, where the triggering to move from the collapsed shape to the expanded shape or vice versa is caused by pneumatic, hydraulic, mechanical or electromechanical means.
29. A medical device as claimed in claims 1 to 28, where the unit cell is made of an arrangement of relatively rigid sections, connected by plastic or elastic deformable joints.
- 20 30. A medical device having a plurality of stable configurations, the device comprised of a plurality of interconnected cells, each cell having a cell structure, the cells including a relatively rigid section and a relatively flexible section interconnected so as to define the cell structure in the form of a multistable spring system having a plurality of stable configurations.
- 25 31. The medical device of claim 30 wherein the cell structure is bistable having two stable configurations.
32. The medical device of claim 31 wherein the cells are constructed and arranged so that the device may be switched between two stable configurations by applying a uniform radially directed force.
- 30 33. The medical device of claim 31 as a tubular stent having two or more configurations including an unexpanded configuration and a fully expanded

configuration, the diameter of the stent in the fully expanded configuration exceeding the diameter of the stent in the unexpanded configuration.

34. The medical device of claim 30 wherein the cells are designed and arranged to provide a range of diameters in step-wise fashion.

5 35. The medical device of claim 34 as a tubular stent having an initial diameter at a first end, a final diameter at a second end and at least one intermediate diameter between the first and second ends, the intermediate diameter differing from the initial and final diameters.

10 36. The medical device of claim 35 wherein the initial and final diameters are the same.

37. A tubular stent having a surface, the stent comprising a plurality of cells having a plurality of stable states, the cells on the surface of the stent, the cells having at least a first stable state and a second stable state, the cells in the second state encompassing a larger area than the cell in the first state, the cells characterized by a negative spring
15 constant, the cells constructed and arranged so that the stent is characterized by a plurality of stable states.

38. The stent of claim 37 wherein the cells are bistable having first and second stable shapes.

39. The stent of claim 38 wherein the cells are arranged and disposed such that the
20 stent has at least two stable states, including a first stable state in which the stent is characterized by a first diameter and a second stable state in which the stent is characterized by a second diameter, the second diameter larger than the first diameter.

40. The stent of claim 38 further having a third stable state, the third stable state having a third diameter different from the first and second diameters.

25 41. The stent of claim 38 wherein the cells are formed from at least two different segments:

a first segment which acts as a relatively rigid support for the cell, and
a second segment which is more pliable than the first segment, the second
segment capable of existing in two distinct states, a first contracted state corresponding to
30 the first stable state of the cell and a second expanded state corresponding to the second stable state of the cell, the first and second segments fixedly connected one to the other.

42. The stent of claim 41 wherein the cells are constructed and arranged so that the stent has two stable states, a contracted state having a first diameter and an expanded state having a second diameter larger than the first diameter.
43. The stent of claim 41 wherein the first and second segments are formed of the same material, the first segment having a first cross-sectional area and the second segment having a second cross-sectional area in excess of the first cross-sectional area.
44. The stent of claim 41 wherein the first and second segments are made of different materials, the material of the first segment being more rigid than the material of the second segment.
45. The stent of claim 41 wherein the first and second segments are made of the same material, the first segments being strengthened by heat treating so as to increase the rigidity of the first segments.
46. The stent of claim 41 having a uniform diameter and having three or more stable states, the diameter of the stent differing in each stable state.
47. The stent of claim 41 constructed and arranged to have three or more stable states, the stent having different diameters in some of the stable states, the stent comprised of a plurality of bistable cells of two or more types, the cell types requiring differing amounts of force to expand.
48. A method of implanting an expandable stent having a plurality of stable configurations comprising the steps of:
- 1) applying the stent to a balloon mounted on a catheter;
 - 2) delivering the stent to a desired bodily location;
 - 3) inflating the balloon so as to expand the stent from a first stable configuration to a desired second stable configuration, the second stable configuration exhibiting a larger diameter than the first stable configuration; and
 - 4) deploying the expanded stent at the desired bodily location.
49. The method of claim 48 wherein the stent is applied to the balloon in the second stable configuration during the applying step and further comprising the step of:
- applying radially pressure inward on the stent so as to urge the stent into the first stable configuration.
50. The method of claim 48 wherein the stent is applied to the balloon in a third

stable state during the applying step, the diameter of the stent in the third stable state intermediate between the diameter in the first state and the diameter in the second state and further comprising the step of:

5 applying radially pressure inward on the stent so as to urge the stent into the first stable configuration.

51. An expandable stent having an initial condition and an expanded condition, the stent having a plurality of diameters along its length in the expanded condition, the stent comprised of a plurality of cells having a plurality of stable states, the cells encompassing different areas in the different states.

10 52. An expandable device comprising one or more multistable loops, the loop having at least a first state and a second state, the loop encompassing a first area in the first state and a second area in the second state, wherein the device is expanded by applying a force thereto.

15 53. The device of claim 52 comprising a first arcuate member having first and second ends and a second arcuate member having first and second ends,
 the first end of the first member in communication with the first end of the second member, and

 the second end of the first member in communication with the second end of the second member,

20 wherein the second member is more pliable than the first, the second member capable of assuming a first stable position and a second stable position.

54. A clamp for securing a bodily member selected from the group consisting of body tissue, body organs, body lumens and body vessels comprising the device of claim 1 and further comprising a triggering means for triggering the device to alter from one state to
25 the other.

55. A tubular graft stent comprising one or more expansion rings, each expansion ring capable of assuming first and second stable configurations,

 the expansion rings formed of a first member and a second member, the second member more pliable than the first member, and having a first and a second stable
30 position, the first stable position corresponding to the first stable configuration and the second stable position corresponding to the second stable configuration, the ring

encompassing a greater area in the second stable configuration than in the first stable configuration,

the stent having a surface, the surface comprising a skin mounted on the expansion rings.

- 5 56. The stent of claim 55 wherein the skin is selected from the group of materials consisting of polymeric materials, human skin, animal skin, human tissue and animal tissue.

57. The stent of claim 56 having two expansion rings, a first expansion ring at a first end of the stent and a second expansion ring at a second end of the stent.

- 10 58. The stent of claim 57 having a first diameter at the first end and a second diameter at the second end.

59. A stent having an unexpanded configuration and an expanded configuration,
the stent having a surface,
the stent comprising:

- 15 a plurality of generally longitudinal, wave-like first members characterized by a first wavelength, and having peaks and troughs; and

a plurality of generally longitudinal wave-like second members characterized by a second wavelength, and having peaks and troughs,

- 20 the second wavelength substantially equal to the first wavelength, the second members capable of stably assuming two positions,

a first position corresponding to the unexpanded configuration in which the first and second members are in phase and

- 25 a second position corresponding to the expanded configuration, in which the first and second members are 180° out of phase, the first members more rigid than the second members,

the first and second longitudinal members disposed on the surface of the stent, the longitudinal first and second member alternating,

each peak of each first member attached to one adjacent peak of a second member in a region of attachment,

- 30 each trough of each first member attached to one adjacent trough of a second member in a region of attachment,

the regions of attachment separated by one wavelength,
whereby the stent can be snapped from the unexpanded configuration to the expanded
configuration by applying a radially outward or tangential force thereto and the stent can
be snapped from the expanded to the unexpanded configuration by applying a radial
5 inward or tangential force thereto.

60. A method of joining together two bodily vessels comprising the steps of:
delivering the stent of claim 40 in a first stable state corresponding to an
unexpanded configuration to a bodily site;

10 expanding the stent to a second stable state, the diameter of the stent exceeding
the diameter of the vessels;

placing the stent over the vessels to be joined; and

contracting the stent to a third stable state, the diameter of the stent in the third
stable state intermediate between the diameter of the stent in the first and second stable
states, whereby the stent rests snugly upon the vessels.

15 61. The method of claim 60, the stent having a first end a second end, further
comprising the steps of:

positioning one or more devices as in claim 52 in the form of an expander ring
inside the vessels and underneath a portion of the stent; and

20 expanding the one or more devices so as to clamp the vessel between the device
and the stent.

62. A method of joining together two bodily vessels comprising the steps of:
delivering the stent of claim 39 in a first stable state corresponding to an
unexpanded configuration to a bodily site;

25 placing each of the bodily vessels over at least a portion of the stent, the diameter
of the vessels exceeding the diameter of the stent in the first stable state; and ;

expanding the stent to a second stable state, the diameter of the stent in the
second stable state chosen so that the vessels fit snugly over the stent.

63. The method of claim 62 further comprising the steps of:

30 positioning one or more collars around the vessels and over a portion of the stent
so as to clamp the vessel in place in between the stent and the collar.

64. A method of joining together a first and a second vessel, the first vessel having an

end and the second vessel having an end, comprising the steps of:

placing a rigid support collar over the end of the second vessel;

placing at least a portion of the first vessel in at least a portion of the second vessel;

5 positioning an expansion device as in claim 52 in the form of an expansion ring interior to the first and second vessels; and

expanding the expansion ring so as to clamp the vessels together.

65. A stent as in claim 37 wherein the cells are expandable from the first to the second stable state, the expansion having a tangential component and an axial
10 component.

66. A bistable valve for opening and closing a tubular device comprising:

1) a conduit, the conduit having an interior, an inner wall and an outer wall;

2) a stop surface extending across the interior of the conduit, the stop surface having an opening within;

15 3) a snap-action bipositional unit cell, the unit cell including a flexible member, the flexible member substantially arcuate, the flexible member having a first end and a second end,

the first end in communication with a triggering means,

the triggering means supported by a support means

20 emanating from the inner wall of the conduit,

the second end anchored to the stop surface,

the bipositional unit cell constructed and arranged so that the flexible member may assume a first position corresponding to a closed position and a second position corresponding to an open position;

25 4) a valve closure member actuated between open and closed position by the flexible member, the valve closure member constructed and arranged so as to completely close the opening in the stop surface when the flexible member is in the closed position, the valve closure member further constructed and arranged so that the opening is open when the flexible member is in the opened position,

30 whereby the conduit may be opened by triggering the triggering means so as to allow the flexible member to move between the closed position and the opened position,

and

the conduit may be closed by triggering the triggering means so as to allow the flexible member to move between the opened state and the close state.

67. The bistable valve of claim 66 wherein the triggering means is a
5 piezoelectric element, the piezoelectric element serving as a restraining means for restraining the flexible member, the piezoelectric element triggering the flexible member to flip by undergoing a small decrease in length upon introducing a small current thereto, thereby releasing the flexible member.

68. The bistable valve of claim 66 wherein the support means is a rigid
10 member relative to the flexible member.

69. The bistable valve of claim 66 wherein the stop surface has two oblique regions, the oblique regions being oblique relative to the longitudinal axis of the tube, with a longitudinal region therebetween, the opening disposed in the longitudinal region.

70. A medical device for use in the human body comprising the bistable valve
15 of claim 66.

71. A medical device for use in controlling urinary incontinence, the device comprising the bistable valve of claim 66.

72. A method of controlling urinary incontinence comprising the steps of:
20 1) inserting a medical device as in claim 71 into a portion of a urethra; and
2) optionally clamping the medical device in place by applying a clamp as described in claim 54 to the outside of the urethra;

wherein urine may be voided by triggering the valve so as to switch it from the closed to the opened position, the valve being triggered so as to close following urination.

25 73. A medical device including at least one multistable unit cell, the multistable unit cell formed from at least four relatively rigid segments, each relatively rigid segment having a first end and a second end, each first end connected to a second end of an adjacent segment by a plastically or elastically deformable hinge and each second end connected to a first end by a plastically or elastically deformable hinge so as to formed a
30 closed cell, whereby the multistable unit cell can be switched between a first stable fully collapsed shape and a second stable fully expanded shape.

74. A medical device as in claim 73 in the form of a stent comprising a plurality of multistable units cells having four relatively rigid segments, the stent having at least two stable configurations including a first fully collapsed configuration having a first area and a second fully expanded configuration having a second area larger than the first area.

- 5 75. A medical device as in claim 74 in the form of a stent wherein the multistable unit cell has:
- a top segment;
 - a bottom segment, the bottom segment including a portion that is substantially parallel to the top segment, the parallel segment having first and second ends, and two
 - 10 oblique portions that are disposed at oblique angles relative to the parallel portion, each oblique portion situated at an end of the parallel portion;
 - a first segment connecting the bottom and top segments
 - and a second segment connecting the bottom and top segments, the first and second segments of substantially equal length, the cell symmetric about an axis that
 - 15 bisects the top and bottom segments.

76. A medical device as in claim 75 in the form of a stent wherein the multistable unit cell assumes a hexagonal shape in its expanded state.

77. A medical device as in claim 74 in the form of a stent wherein the multistable unit cell has:
- 20 a curved top segment;
 - a bottom segment, the bottom segment substantially parallel to the top segment,
 - a first segment connecting the bottom and top segments
 - and a second segment connecting the bottom and top segments, the first and second segments of substantially equal length, the cell symmetric about an axis that
 - 25 bisects the top and bottom segments.








Fig. 1a**Fig. 1b****Fig. 1c****Fig. 3****Fig. 2****Fig. 4****Fig. 5a**






Fig. 5b**Fig. 6****Fig. 7****Fig. 8****Fig. 9**

Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16








Fig. 17**Fig. 18****Fig. 19****Fig. 20**

Fig. 21a




Fig. 21b




Fig. 22b

Fig. 22a





Fig. 23




Fig. 24b




Fig. 24a




Fig. 24d





Fig. 24c



PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61F 2/06, A61B 17/11, A61F 2/00, F16K 31/00		A3	(11) International Publication Number: WO 98/32412 (43) International Publication Date: 30 July 1998 (30.07.98)
(21) International Application Number: PCT/US98/01310 (22) International Filing Date: 23 January 1998 (23.01.98) (30) Priority Data: 60/036,359 24 January 1997 (24.01.97) US (71) Applicant (for all designated States except US): SCIMED LIFE SYSTEMS, INC. [US/US]; One SciMed Place, Maple Grove, MN 55311-1566 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): BESSELINK, Petrus, Antonius [NL/NL]; Gronausestraat 1220, NL-7534 AT Enschede (NL). (74) Agents: ARRETT, Oliver, F. et al.; Vidas, Arrett & Steinkraus, Suite 2000, 6109 Blue Circle Drive, Minnetonka, MN 55343-9131 (US).			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 12 November 1998 (12.11.98)
(54) Title: BISTABLE SPRING CONSTRUCTION FOR A STENT AND OTHER MEDICAL APPARATUS			
(57) Abstract <p>The present invention is directed to bistable cells and their use in devices, particularly medical devices such as stents, clamps and valves. An expandable stent formed of a plurality of bistable cells is described. The stent has two or more stable configurations, including a first stable configuration with a first diameter and a second stable configuration with a second, larger diameter. A valve comprising a bistable cell for use in eliminating incontinence is also disclosed.</p>			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 98/01310

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 A61F2/06 A61B17/11 A61F2/00 F16K31/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 A61F A61B F16K F16L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 18359 A (FOUERE) 20 June 1996 see abstract; figures 1,2 ---	1,11-13, 17-21, 28-33
X	WO 95 09584 A (GUERBET) 13 April 1995	1,11-13, 21, 28-33, 55-57 58
Y	see page 9, line 26 - page 10, line 12; figures ---	
X	WO 96 09013 A (WAKE FOREST INIVERSITY) 28 March 1996 see abstract; figures 10,14 --- -/--	1,11-13, 30-33
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "G" document member of the same patent family		
Date of the actual completion of the international search 4 September 1998		Date of mailing of the international search report 16.09.98
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Neumann, E

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 98/01310

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 562 690 A (GREEN ET AL) 8 October 1996	1,54
A	see column 5, line 36 - column 7, line 13; figures 1-8	7,8
P,X	US 5 695 516 A (FISCHELL ET AL.) 9 December 1997	1,9, 11-13, 15,16, 28-33
A	see the whole document	2-4
P,X	WO 97 04721 A (MEDSTENT) 13 February 1997	1,4, 11-13, 28-33
	see page 7, line 3 - line 33; figures 1,3,8-10	
Y	EP 0 587 197 A (ANGIOMED) 16 March 1994 see claim 7	58
A	US 5 234 448 A (WHOLEY ET AL.) 10 August 1993 see the whole document	7,8,54
A	WO 95 31945 A (SCIMED LIFE SYSTEMS) 30 November 1995	6
A	EP 0 326 426 A (JAPAN MEDICAL SUPPLY) 2 August 1989	
X	WO 96 41589 A (COOK WILLIAM EUROP ;KAVTELADZE ZAZA ALEXANDROVICH (RU); KORSHOK AL) 27 December 1996	51
A	see page 16, line 10 - line 35; figures	37-39, 41-43, 46,47
X	WO 93 22986 A (SCHNEIDER USA INC) 25 November 1993 see page 13, line 16 - line 26	51
A		37-42,47
A	EP 0 688 545 A (TERUMO CORP) 27 December 1995 see abstract; figures	37-39, 41-43, 45,47,65
A	EP 0 364 787 A (EXPANDABLE GRAFTS PARTNERSHIP) 25 April 1990 see column 1, line 25 - line 50; figures	37-39,65
	-/--	

INTERNATIONAL SEARCH REPORT

In: International Application No
PCT/US 98/01310

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 664 107 A (NAZARI STEFANO) 26 July 1995 see column 3, line 44 - column 4, line 37; figures ---	52
X	US 4 994 071 A (MACGREGOR DAVID C) 19 February 1991 see column 3, line 54 - column 4, line 18; figures ---	52
X	GB 2 081 173 A (BEHAR YVES;ALBERTINI PROSPER JEAN; GEFFROY JEAN LOUIS) 17 February 1982 see abstract; figures ---	52
A	US 3 508 587 A (MAUCH HANS A) 28 April 1970 see column 3, line 6 - line 48; figure 2A ---	52,53
X	EP 0 734 698 A (VARIOMED AG) 2 October 1996 see the whole document ---	59
A	EP 0 679 372 A (ADVANCED CARDIOVASCULAR SYSTEM) 2 November 1995 see figures ---	59
A	WO 96 03942 A (RAM MICHAEL J ;KALB IRVIN M (US); SHAW ROBERT H (US)) 15 February 1996 see page 10, line 14 - page 11, line 14; figures ---	66,67, 70,71
A	FR 2 642 812 A (CROUZET SA) 10 August 1990 see abstract; figures ---	66-68
A	EP 0 636 345 A (SENTINEL MEDICAL INC) 1 February 1995 see abstract; figures ---	66,70,71
A	US 3 069 125 A (J.C. HEWITT, JR.) 18 December 1962 see the whole document ---	66,68,69
X	WO 96 29028 A (GRASS ANTHONY JAMES ;UNIV LONDON (GB); ADISESHIAH MOHAN (GB)) 26 September 1996 see page 3, paragraph 1 - paragraph 3; figures ---	73,74
A	see page 6, last paragraph - page 7, paragraph 2 ---	75
X	EP 0 744 164 A (COOK INC) 27 November 1996 see column 6, line 15 - line 37; figures ---	73,74
A	see column 12, line 36 - line 42 ---	75
	--- -/--	

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 98/01310

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 169 515 A (LIFELINE LTD) 16 July 1986 see the whole document	73
A	---	74,75
X	EP 0 421 729 A (MEDTRONIC INC) 10 April 1991 see abstract; figures	73,74
A	---	
A	US 5 141 360 A (ZEMAN DAVID) 25 August 1992 see column 5, line 34 - line 68; figure 3	73-76
A	---	
A	WO 95 32757 A (NITINOL MEDICAL TECHNOLOGIES I) 7 December 1995 see abstract; figures	73-76

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 98/01310

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 48-50 60-64 72
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US 98/01310

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-36, 54-58

A medical device containing at least one unit cell with one relatively flexible segment and one relatively rigid segment

1.1 Claims 1,2,5-29

A unit cell with symmetrical load-displacement

1.2 Claims 1,3,5-29

A unit cell with asymmetrical load-displacement characteristic, most stable in expanded state

1.3 Claims 1,4-29

A unit cell with asymmetrical load-displacement characteristic, most stable in collapsed state

1.4 Claims 30-36

A medical device with a multistable spring system

1.5 Claim 1,54

A clamp

1.6 Claims 55-58

A graft stent with expansion rings

2. Claims: 37-47,65

A stent with a negativ spring constant

3. Claim : 51

A stent with a plurality of diameters

4. Claims: 52, 53

An expandable device

5. Claim : 59

A stent with wavelike members

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US 98/01310

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

6. Claims: 66-71

A bistable valve

7. Claims: 73-77

A medical device with a cell with four rigid segments

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/01310

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9618359 A	20-06-1996	FR 2728156 A AU 4119896 A EP 0843538 A	21-06-1996 03-07-1996 27-05-1998
WO 9509584 A	13-04-1995	FR 2710834 A AT 162065 T AU 7858594 A CA 2173500 A DE 69407984 D DE 69407984 T EP 0722304 A ES 2115262 T JP 9503141 T	14-04-1995 15-01-1998 01-05-1995 13-04-1995 19-02-1998 03-09-1998 24-07-1996 16-06-1998 31-03-1997
WO 9609013 A	28-03-1996	US 5702419 A AU 3418395 A CA 2200489 A	30-12-1997 09-04-1996 28-03-1996
US 5562690 A	08-10-1996	NONE	
US 5695516 A	09-12-1997	NONE	
WO 9704721 A	13-02-1997	AU 6511196 A EP 0840578 A NO 980302 A PL 324781 A US 5776181 A	26-02-1997 13-05-1998 24-03-1998 08-06-1998 07-07-1998
EP 587197 A	16-03-1994	DE 9014230 U AT 107495 T DE 9116936 U DE 59102001 D DK 481365 T EP 0481365 A ES 2057709 T JP 4256759 A	21-11-1991 15-07-1994 01-09-1994 28-07-1994 07-11-1994 22-04-1992 16-10-1994 11-09-1992
US 5234448 A	10-08-1993	AT 156986 T CA 2090763 A,C CA 2173636 A	15-09-1997 29-08-1993 29-08-1993

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No
PCT/US 98/01310

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5234448 A		DE 69313162 D EP 0558352 A EP 0781528 A US 5254127 A	25-09-1997 01-09-1993 02-07-1997 19-10-1993
WO 9531945 A	30-11-1995	CA 2190012 A EP 0759730 A JP 10500595 T	30-11-1995 05-03-1997 20-01-1998
EP 326426 A	02-08-1989	JP 1192367 A JP 2561853 B CA 1307885 A DE 68920055 D DE 68920055 T US 4950258 A	02-08-1989 11-12-1996 29-09-1992 02-02-1995 11-05-1995 21-08-1990
WO 9641589 A	27-12-1996	AU 6121896 A EP 0836450 A	09-01-1997 22-04-1998
WO 9322986 A	25-11-1993	AU 693054 B AU 1905397 A AU 678350 B AU 3789793 A CA 2134090 A,C CA 2179668 A DE 9390115 U EP 0639958 A JP 2660101 B JP 7502673 T US 5645559 A	18-06-1998 19-06-1997 29-05-1997 13-12-1993 25-11-1993 09-11-1993 22-12-1994 01-03-1995 08-10-1997 23-03-1995 08-07-1997
EP 0688545 A	27-12-1995	JP 8000738 A JP 8196642 A JP 8215318 A	09-01-1996 06-08-1996 27-08-1996
EP 0364787 A	25-04-1990	AU 623438 B AU 4248589 A CA 1322628 A GR 3003987 T JP 2174859 A	14-05-1992 12-04-1990 05-10-1993 16-03-1993 06-07-1990

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/US 98/01310

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0364787 A		JP 2680901 B US 5195984 A	19-11-1997 23-03-1993
EP 0664107 A	26-07-1995	IT 1269443 B US 5554183 A	01-04-1997 10-09-1996
US 4994071 A	19-02-1991	NONE	
GB 2081173 A	17-02-1982	FR 2487086 A DE 3127446 A JP 57052015 A	22-01-1982 06-05-1982 27-03-1982
US 3508587 A	28-04-1970	NONE	
EP 0734698 A	02-10-1996	DE 19512066 A DE 19540851 A AT 169484 T DE 19516191 A JP 9010318 A	28-11-1996 07-05-1997 15-08-1998 06-02-1997 14-01-1997
EP 0679372 A	02-11-1995	CA 2147709 A JP 8126704 A US 5725572 A	26-10-1995 21-05-1996 10-03-1998
WO 9603942 A	15-02-1996	US 5476434 A AU 3320695 A CA 2195949 A CN 1159155 A EP 0793465 A JP 10507652 T US 5509889 A US 5704353 A	19-12-1995 04-03-1996 15-02-1996 10-09-1997 10-09-1997 28-07-1998 23-04-1996 06-01-1998
FR 2642812 A	10-08-1990	NONE	
EP 0636345 A	01-02-1995	AU 677061 B AU 6746894 A CA 2127637 A JP 7313520 A US 5562692 A	10-04-1997 02-02-1995 27-01-1995 05-12-1995 08-10-1996

INTERNATIONAL SEARCH REPORT

Information on patent family members

In tional Application No

PCT/US 98/01310

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0636345 A		US 5735815 A	07-04-1998
US 3069125 A	18-12-1962	NONE	
WO 9629028 A	26-09-1996	AU 5116896 A CA 2216522 A EP 0817599 A	08-10-1996 26-09-1996 14-01-1998
EP 0744164 A	27-11-1996	AU 5240596 A CA 2176987 A JP 9099095 A US 5707376 A	19-12-1996 26-11-1996 15-04-1997 13-01-1998
GB 2169515 A	16-07-1986	NONE	
EP 0421729 A	10-04-1991	CA 2026604 A DE 69024901 D DE 69024901 T IE 73670 B JP 3151983 A	03-04-1991 29-02-1996 14-08-1996 02-07-1997 28-06-1991
US 5141360 A	25-08-1992	US 5292073 A US 5263791 A US 5224796 A	08-03-1994 23-11-1993 06-07-1993
WO 9532757 A	07-12-1995	US 5540712 A CA 2191307 A EP 0788390 A JP 10504200 T US 5746765 A	30-07-1996 07-12-1995 13-08-1997 28-04-1998 05-05-1998